MAR 1 4 2008

Customer No. 24498 Attorney Docket No. PU030177 US

Office Action Date: December 26, 2007

## Listing and Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

A method, comprising: 1. (Previously Presented)

scanning, by a wireless local area network scanner in a wireless device, to detect the presence of a wireless local area network WLAN;

detecting the presence of said wireless local area network by employing said wireless local area network scanner to identify energy fluctuations without a wireless local area network baseband circuit being activated to process data;

contacting a base station of said wireless local area network by the wireless local area network baseband circuit in said wireless device in response to detection of said wireless local area network to request location of said base station; and

receiving location of said wireless local area network.

- The method according to claim 1, further comprising 2. (Previously Presented) logging, on said wireless device, said location of said base station for future reference.
- The method of claim 1, wherein said location comprises a map 3. (Original) coordinate location of said base station.
- The method of claim 1, wherein said location comprises one of a street 4. (Original) address and longitude/latitude coordinates for said base station.

Customer No. 24498

Attorney Docket No. PU030177 US

Office Action Date: December 26, 2007

- 5. (Previously Presented) The method of claim 1, wherein said contacting further comprises comparing a media access control MAC address of said base station to a database of known locations of base stations of wireless local area networks and not requesting a location if the contacted said base station is already in said database
- 6. (Original) The method of claim 2, wherein said logging of said location is one of an automated logging and a manual logging.
- 7. (Original) The method according to claim 1, wherein said location comprises global position coordinates.
- 8. (Original) The method of claim 1, wherein said detecting comprises detecting signature sequences from a wireless local area network.
- 9. (Currently Amended) A wireless device configured to carry out the following steps:

scanning to detect presence of a wireless local area network WLAN;

detecting the presence of said wireless local area network by identifying energy fluctuations of a wireless local area network signal-prior-to\_without performing carrier recovery to detect the presence of said wireless local area network;

requesting a base station of said wireless local area network detected for a location of said base station; and

receiving and logging said location, on said wireless device, of said base station of said wireless local area network.

Customer No. 24498

Attorney Docket No. PU030177 US

Office Action Date: December 26, 2007

10. (Original) The wireless device of claim 9, wherein said location comprises a

map location of said base station.

11. (Previously Presented) The wireless device of claim 9, wherein said location

comprises a street address for said base station.

12. (Previously Presented) The wireless device of claim 9, wherein said location

comprises global position coordinates

13. (Canceled)

14. (Previously Presented) The wireless device of claim 9, wherein said detecting

comprises detection of an energy signature from said wireless local area network.

15. (Previously Presented) The wireless device of claim 9, further comprising

the step of displaying a location of a base station of a wireless local area network logged

previously that is near said wireless device.

16. (Previously Presented) A mobile device operable to communicate with a

wireless communication network and a wireless local area network (WLAN), configured for

carrying out the following steps:

scanning to detect presence of a wireless local area network WLAN by a wireless

local area network scanner in a wireless device;

Customer No. 24498 Attorney Docket No. PU030177 U\$ Office Action Date: December 26, 2007

detecting presence of said wireless local area network by employing said wireless local area network scanner to identify energy fluctuations without a wireless local area network baseband circuit being activated to process data;

contacting a base station of said wireless local area network detected to request location of said base station by the wireless local area network baseband circuit in said wireless device in response to detection of said wireless local area network; and

17. (Previously Presented) The mobile device of claim 16, further comprising logging said location of said base station for future reference.

receiving location of said wireless local area network.

- 18. (Original) The mobile device of claim 16, wherein said location comprises a map coordinate location of said base station.
- 19. (Original) The mobile device of claim 16, wherein said location comprises a street address for said base station.
- 20. (Original) The mobile device of claim 16, wherein said location comprises global position coordinates.
- 21. (Previously Presented) The mobile device of claim 16, further comprising displaying a location of a logged bases station of a wireless local area network near a location input by a user.